

QUICKSEAM BATTEN COVER (510)

1. Identification of the substance/preparation and of the company/undertaking

1.1 Identification of the substance or preparation:

Synonyms: none
 CAS No. : N.A.
 EC index No. : N.A. NFPA code : N.D.
 EINECS No. : N.A. Molecular weight : N.A.
 RTECS No. : N.A. Formula : N.A.

1.2 Use of the substance or the preparation:

Construction: sealing compound

1.3 Company/undertaking identification:

Firestone Building Products
 Ikaroslaan 75
 B-1930 Zaventem
 Tel. : +32 2 711 44 50
 Fax : +32 2 721 27 18
 Email: info@fbpe.be

1.4 Telephone number for emergency:

+32 70 245 245
 Poison Centre
 p/a Militair Hospitaal Koningin Astrid, Bruynstraat, B-1120 Brussel

2. Composition/information on ingredients

Hazardous ingredients	CAS No. EINECS/ELINCS No.	Conc. in %	Hazard symbol	Risks (R-phrases)
None	- -	-	-	-

3. Hazards identification

- No hazard classification in accordance with directives 67/548/EEC and 1999/45/EC

4. First aid measures

4.1 Eye contact:

- Consult a doctor/medical service if irritation persists
 - Rinse immediately with water

4.2 Skin contact:

- Consult a doctor/medical service if irritation persists
 - Wash with water and soap
 - Use waterless hand cleaner

4.3 After inhalation:

- Consult a doctor/medical service if breathing problems develop
 - Remove the victim into fresh air
 - Unconscious: maintain adequate airway and respiration

4.4 After ingestion:

- Consult a doctor/medical service if you feel unwell
 - Not applicable

QUICKSEAM BATTEN COVER (510)

5. Fire-fighting measures

5.1 Suitable extinguishing media:

- Water
- Polyvalent foam
- ABC powder
- Carbon dioxide

5.2 Unsuitable extinguishing media:

- No data available

5.3 Special exposure hazards:

- Not easily combustible
- On heating: release of carcinogenic products
- On burning: release of toxic and corrosive gases/vapours (nitrous vapours, sulphur oxides, carbon monoxide - carbon dioxide)

5.4 Instructions:

- Dilute toxic gases with water spray

5.5 Special protective equipment for firefighters:

- Heat/fire exposure: compressed air/oxygen apparatus
- Protective clothing for exposure to chemicals

6. Accidental release measures

6.1 Personal protection/precautions:

See heading 8.2/8.3/13

6.2 Environmental precautions:

- Contain leaking substance

6.3 Methods for cleaning up:

- Pick-up the material
- Clean contaminated surfaces with an excess of water
- Wash clothing and equipment after handling

7. Handling and storage

7.1 Handling:

- Observe normal hygiene standards

7.2 Storage:

- Store at room temperature
- Keep out of direct sunlight
- Limited time of storage
- Store in a dry area
- Keep away from: heat sources

Storage temperature	: 15/25	°C
Quantity limits	: N.D.	kg
Storage life	: < 365	days
Materials for packaging	:	
- suitable	:no data available	

- to avoid :no data available

7.3 Specific uses:

- See information supplied by the manufacturer

QUICKSEAM BATTEN COVER (510)

8. Exposure controls/Personal protection

8.1 Exposure limit values:

TLV-TWA	: not listed
TLV-STEL	: not listed
TLV-Ceiling	: not listed
OES-LTEL	: not listed
OES-STEL	: not listed
MEL-LTEL	: not listed
MEL-STEL	: not listed
MAK	: not listed
TRK	: not listed
MAC-TGG 8 h	: not listed
MAC-TGG 15 min.	: not listed
MAC-Ceiling	: not listed
VME-8 h	: not listed
VLE-15 min.	: not listed
GWBB-8 h	: not listed
GWK-15 min.	: not listed
Momentary value	: not listed
EC	: not listed
EC-STEL	: not listed

Sampling methods:

- No data available

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- No data available

8.2.2 Environmental exposure controls: see heading 13

8.3 Personal protection:

8.3.1 respiratory protection:

- Respiratory protection not required in normal conditions

8.3.2 hand protection:

- Gloves
Suitable materials: No data available
- Breakthrough time: N.D.

8.3.3 eye protection:

- Safety glasses

8.3.4 skin protection:

- Protective clothing
Suitable materials: No data available

QUICKSEAM BATTEN COVER (510)

9. Physical and chemical properties

9.1 General information:

Appearance (at 20°C) : Solid
Odour : Odourless
Colour : Black

9.2 Important health, safety and environmental information:

pH value : N.D.
Boiling point/boiling range : N.D. °C
Flashpoint : > 200 °C
Explosion limits : N.D. vol% (°C)
Vapour pressure (at 20°C) : N.D. hPa
Vapour pressure (at 50°C) : N.D. hPa
Relative density (at 20°C) : 0.97
Water solubility : Insoluble
Soluble in : N.D.
Relative vapour density : N.D.
Viscosity : N.D. Pa.s
Partition coefficient n-octanol/water : N.D.
Evaporation rate :
 ratio to butyl acetate : N.D.
 ratio to ether : N.D.

9.3 Other information:

Melting point/melting range : N.D. °C
Auto-ignition point : N.D. °C
Saturation concentration : N.D. g/m³

10. Stability and reactivity

10.1 Conditions to avoid/reactivity:

- Stable under normal conditions

10.2 Materials to avoid:

- Keep away from: heat sources

10.3 Hazardous decomposition products:

- On heating: release of carcinogenic products
- On burning: release of toxic and corrosive gases/vapours (nitrous vapours, sulphur oxides, carbon monoxide - carbon dioxide)
- Prolonged storage: release of carcinogenic products

QUICKSEAM BATTEN COVER (510)

11. Toxicological information

11.1 Acute toxicity:

LD50 oral rat	: N.D.	mg/kg
LD50 dermal rat	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LC50 inhalation rat	: N.D.	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

11.2 Chronic toxicity:

EC carc. cat.	: not listed
EC muta. cat.	: not listed
EC repr. cat.	: not listed
Carcinogenicity (TLV)	: not listed
Carcinogenicity (MAC)	: not listed
Carcinogenicity (VME)	: not listed
Carcinogenicity (GWBB)	: not listed
Carcinogenicity (MAK)	: not listed
Mutagenicity (MAK)	: not listed
Teratogenicity (MAK)	: not listed
IARC classification	: not listed

11.3 Routes of exposure: ingestion, inhalation, eyes and skin

11.4 Acute effects/symptoms:

- AFTER EYE CONTACT
- Mechanical irritation
- Redness of the eye tissue

11.5 Chronic effects:

- Not listed in carcinogenicity class (IARC,EC,TLV,MAK)
- Not listed in mutagenicity class (EC,MAK)
- Not classified as toxic to reproduction (EC)

QUICKSEAM BATTEN COVER (510)

12. Ecological information

12.1 Ecotoxicity:

- No data available

12.2 Mobility:

- Volatile organic compounds (VOC): N.D. %
- Insoluble in water

For other physicochemical properties see heading 9

12.3 Persistence and degradability:

- biodegradation BOD₅ : N.D. % ThOD
- water : - No data available
- soil : T ½: N.D. days

12.4 Bioaccumulative potential:

- log P_{ow} : N.D.
- BCF : N.D.

12.5 Other adverse effects:

- WGK : N.D.
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : no data available
- Effect on waste water purification : no data available

13. Disposal considerations

13.1 Provisions relating to waste:

- Waste material code (75/442/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 17 09 04 (mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03)

13.2 Disposal methods:

- Remove to an authorized waste treatment plant

13.3 Packaging/Container:

- No available data

QUICKSEAM BATTEN COVER (510)

14. Transport information

- 14.1 Classification of the substance in compliance with UN Recommendations
- | | | |
|----------------------|---|-------------|
| UN number | : | - |
| CLASS | : | NOT SUBJECT |
| SUB RISKS | : | |
| PACKING | : | |
| PROPER SHIPPING NAME | : | |
- 14.2 ADR (transport by road)
- | | | |
|-----------------------|---|-------------|
| CLASS | : | NOT SUBJECT |
| PACKING | : | |
| CLASSIFICATION CODE | : | |
| DANGER LABEL TANKS | : | |
| DANGER LABEL PACKAGES | : | |
- 14.3 RID (transport by rail)
- | | | |
|-----------------------|---|-------------|
| CLASS | : | NOT SUBJECT |
| PACKING | : | |
| CLASSIFICATION CODE | : | |
| DANGER LABEL TANKS | : | |
| DANGER LABEL PACKAGES | : | |
- 14.4 ADNR (transport by inland waterways)
- | | | |
|-----------------------|---|-------------|
| CLASS | : | NOT SUBJECT |
| PACKING | : | |
| CLASSIFICATION CODE | : | |
| DANGER LABEL TANKS | : | |
| DANGER LABEL PACKAGES | : | |
- 14.5 IMDG (maritime transport)
- | | | |
|------------------|---|-------------|
| CLASS | : | NOT SUBJECT |
| SUB RISKS | : | |
| PACKING | : | |
| MFAG | : | |
| EMS | : | |
| MARINE POLLUTANT | : | |
- 14.6 ICAO (air transport)
- | | | |
|---|---|-------------|
| CLASS | : | NOT SUBJECT |
| SUB RISKS | : | |
| PACKING | : | |
| PACKING INSTRUCTIONS PASSENGER AIRCRAFT | : | |
| PACKING INSTRUCTIONS CARGO AIRCRAFT | : | |
- 14.7 Special precautions in connection with transport
- | | | |
|--|---|--|
| | : | not restricted for any mode of international transport |
|--|---|--|

15. Regulatory information

Classification according to directives 67/548/EEC and 1999/45/EC

NOT APPLICABLE

QUICKSEAM BATTEN COVER (510)

16. Other information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
(*) = INTERNAL CLASSIFICATION (NFPA)

Exposure limits:

TLV : Threshold Limit Value - ACGIH USA
OES : Occupational Exposure Standards - United Kingdom
MEL : Maximum Exposure Limits - United Kingdom
MAK : Maximale Arbeitsplatzkonzentrationen - Germany
TRK : Technische Richtkonzentrationen - Germany
MAC : Maximale aanvaarde concentratie - The Netherlands
VME : Valeurs limites de Moyenne d'Exposition - France
VLE : Valeurs limites d'Exposition à court terme - France
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium
GWK : Grenswaarde kortstondige blootstelling - Belgium
EC : Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalable fraction = **T**: Total dust = **E**: Einatembarer Aerosolanteil
R : Respirable fraction = **A**: Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

a:	aerosol	r:	rook/Rauch	(fume)
d:	damp (vapour)	st:	stof/Staub	(dust)
du:	dust	ve:	vezel	(fibre)
fa:	Faser (fibre)	va:	vapour	
fi:	fibre	om:	oil mist	
fu:	fume	on:	olienevel/Ölnebel	(oil mist)
p:	poussière (dust)	part:	particles	

Chronic toxicity:

K : List of the carcinogenic substances and processes - The Netherlands