

## RubberCover™ QuickSeam Batten Cover Strip

### 1. Description

The Firestone QuickSeam Batten Cover strip is a 152 mm wide semi-cured EPDM strip laminated to a QuickSeam tape. The strip is used to cover and seal butt-jointed RubberCover™ membranes.

### 2. Preparation

The RubberCover™ EPDM surfaces must be prepared with QuickPrime Plus, using a QuickScrubber tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

### 3. Application

Place the roll of Cover strip on the membrane, positioned so it unrolls from the top of the roll (release paper will be on top) and center the cover strip over the exposed membrane edge(s). Unroll the cover strip onto the clean and primed surface. Advance the roll keeping the strip centered over the membrane edge(s) and peel the release paper as you apply the strip.

### 4. Coverage

In accordance with length of seam to be covered. Adjoining QuickSeam Batten Cover strips require an overlap of 25 mm and a cover patch.

### 5. Characteristics

Technical	EPDM Flashing	QuickSeam Tape
■ Base	EPDM	Rubber polymer
■ Colour	Black	Black
■ Solvents	None	None
■ Solids	100 %	100 %
■ State	Semi-cured	Cured
■ Thickness	1.02 mm	0.88 mm
■ Width (mm)	152 mm	156 mm

### 6. Packaging / Storage / Shelf Life

**Packaging:** 7.62 m rolls, 8 rolls per carton.

**Storage:** Store in original unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

**Shelf Life:** 12 months can be expected if stored in above-mentioned conditions. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories. Quality and applicability should thus always be verified: QuickSeam Batten Cover Strip can be used only as long as the release paper can easily be removed from the tape without tearing the paper apart.

### 7. Precautions

Refer to Material Safety Data Sheet.

