

RubberCover™ QuickSeam Corner Flashing

1. Description

QuickSeam Corner Flashing is a 216 mm in diameter round piece of uncured EPDM FormFlash factory laminated to QuickSeam Tape. It is designed to flash outside corners or to be used as a cover patch where appropriate.

2. Preparation

The RubberCover™ EPDM surfaces and/or mating surfaces must be prepared with QuickPrime Plus, using a QuickScrubber tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

3. Application

On cold days with ambient temperature below 5°C, the use of a heat gun is recommended to warm the QuickSeam Corner Flashing and to ensure good formability. On normal days, pre-heating of the product is not necessary.

4. Coverage

One piece a corner.

5. Characteristics

Technical	EPDM Flashing	QuickSeam Tape
■ Base	EPDM	Rubber polymer
■ Colour	Black	Black
■ Solvents	None	None
■ Solids	100 %	100 %
■ State	Uncured	Cured
■ Thickness	1.6 mm	0.6 mm
■ Width	216 mm	216 mm

6. Packaging / Storage / Shelf Life

Packaging: 20 Corner Flashings per carton

Storage: Store in original unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

Shelf Life: 12 months, when stored in above-mentioned conditions. Shelf life will be reduced if exposed to higher temperatures.

7. Precautions

Refer to Material Safety Data Sheet.

